

Product datasheet

Specifications



APC Back-UPS, 650VA, Tower, 230V, 4 IEC C13 Outlets , User Replaceable Battery

BK650-AS

Overview

Lead Time Usually in Stock

Main

Main Input Voltage	230 V
Main Output Voltage	230 V
Rated Power In W	400 W
Rated Power In Va	650 VA
Product Or Component Type	Uninterruptible power supply (UPS)
Input Connection Type	IEC 60320 C14
Output Connection Type	3 IEC 60320 C13 1 IEC 60320 C13 surge
Cable Length	1.83 m
Number Of Cables	2
Battery Type	Lead-acid battery
Provided Equipment	CD with software Documentation CD 1 x detachable 1.2 m IEC power cord 1 x detachable 1.8 m IEC power cord Telephone cable USB cable Warranty card

Batteries & Runtime

Run Time	View Runtime Graph
Efficiency	View Efficiency Graph
Number Of Battery Filled Slots	0
Number Of Battery Free Slots	0
Battery Recharge Time	8 h
Number Of Battery Replacement Quantity	1
Battery Charger Power	12 W rated
Battery Power In Vah	95 VAh runtime
Battery Life	4...6 year(s)
Replacement Battery	BATT17-1209 RBC17

Extended Runtime	0
------------------	---

General

Number Of Power Module Free Slots	0
-----------------------------------	---

Number Of Power Module Filled Slots	0
-------------------------------------	---

Redundant	No
-----------	----

Physical

Colour	Beige
--------	-------

Height	16.5 cm
--------	---------

Width	9.1 cm
-------	--------

Depth	28.4 cm
-------	---------

Net Weight	6.04 kg
------------	---------

Mounting Location	Front
-------------------	-------

Mounting Preference	No preference
---------------------	---------------

Mounting Mode	Not rack-mountable
---------------	--------------------

Two Post Mountable	0
--------------------	---

Usb Compatible	No
----------------	----

Input

Network Frequency	50/60 Hz +/- 3 Hz auto-sensing
-------------------	--------------------------------

Input Voltage Limits	160...282 V adjustable 180...260 V
----------------------	---------------------------------------

Output

Maximum Configurable Power In W	400 W
---------------------------------	-------

Ups Type	Standby
----------	---------

Wave Type	Stepped approximation to a sinewave
-----------	-------------------------------------

Maximum Configurable Power In Va	650 VA
----------------------------------	--------

Conformance

Product Certifications	A-Tick C-Tick CE GOST NEMKO
------------------------	---

Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018
-----------	--

Equipment Protection Policy	Lifetime : \$100000 Lifetime : 50000 GBP
-----------------------------	---

Environmental

Ambient Air Temperature For Operation	0...40 °C
---------------------------------------	-----------

Relative Humidity	5...95 %
-------------------	----------

Operating Altitude	0...30000 ft
--------------------	--------------

Ambient Air Temperature For Storage	-15...45 °C
Storage Relative Humidity	5...95 %
Storage Altitude	0.00...4572.00 m
Acoustic Level	45 dBA
Heat Dissipation	0 Btu/h

Communications & Management

Control Panel	LED status display with on line : on battery : replace battery and overload indicators
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Surge Protection and Filtering

Surge Energy Rate	320 J
-------------------	-------

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	49.4 cm
Package 1 Width	41.5 cm
Package 1 Length	18.5 cm
Package 1 Weight	7.32 kg
Scc14	10731304224430

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

Sustainability


Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

[Learn more about Green Premium >](#)




Energy Efficient Take-back Transparency RoHS/REACH


Resource performance

 Energy Efficient Product

 Take-Back Program Available

Well-being performance

 Mercury Free

 Rohs Exemption Information [Yes](#)

Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

Environmental Disclosure [Product Environmental Profile](#)

Circularity Profile [End of Life Information](#)
